华润微电子(重庆)有限公司

CRJQ74N60G2F

SJMOS N-MOSFET 600V, 70mΩ, 39A

Features

- CRM(CQ) Super_Junction technology
- Much lower Ron*A performance for On-state efficiency
- Better efficiency due to very low FOM
- Ultra-fast body diode
- Qualified for industrial grade applications according to JEDEC

Product Summary

$V_{DS,min}$	600V
$R_{DS(on),typ}$	70mΩ
I_D	39A

Applications


- LED/LCD/PDP TV and monitor Lighting
- Solar/Renewable/UPS-Micro Inverter System
- Charger
- Power Supply


100% DVDS Tested

100% Avalanche Tested

RoHS

HF





Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRJQ74N60G2F	CRJQ74N60G2F	TO-247-3L	Tube	N/A	N/A	25pcs

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Drain-source voltage	V_{DS}	600	V
Continuous drain current [1)] T_C = 25°C T_C = 100°C	I_D	 39 25	A
Pulsed drain current [2)](T_C = 25°C, t_p limited by $T_{j,max}$)	$I_{D,pulse}$	117	A
Avalanche energy, single pulse (L=30mH)	E_{AS}	520	mJ
MOSFET dv/dt ruggedness	dv/dt	50	V/ns
Gate-Source voltage	V_{GS}	±30	V
Power dissipation (T_C = 25°C)	P_{tot}	318	W
Continuous diode forward current(T_C = 25°C)	I_S	39	A
Diode pulse current [2)] (T_C = 25°C)	$I_{S,pulse}$	117	A
Recovery diode dv/dt [3)]	dv/dt	50	V/ns
Operating junction and storage temperature	T_j , T_{stg}	-55...+150	°C

1) Limited by $T_{j,max}$. Maximum Duty Cycle D = 0.50

2) Pulse width t_p limited by $T_{j,max}$

3) Identical low side and high side switch with identical R_g

©China Resources Microelectronics (Chongqing) Limited

Thermal Resistance

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Thermal resistance, junction – case	R_{thJC}	-	0.28	0.39	°C/W	
Thermal resistance, junction – ambient	R_{thJA}	-	-	48	°C/W	

Electrical Characteristic (at T_j = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV_{DSS}	600	-	-	V	V_{GS}=0V,I_D=250μA
Gate threshold voltage	$V_{GS(th)}$	3.2	-	4.6	V	V_{DS}=V_{GS},I_D=250μA
Zero gate voltage drain current	I_{DSS}	-	-	5	μA	V_{DS}=600V,V_{GS}=0V T_j=25°C
		-	500	-		T_j=150°C
Gate-source leakage current	I_{GSS}	-	-	±100	nA	V_{GS}=±30V,V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$	-	70	77	mΩ	V_{GS}=10V,I_D=23A, T_j=25°C
		-	182	-		T_j=150°C
Transconductance	g_{fs}	-	28	-	S	V_{DS}=20V,I_D=23A
Dynamic Characteristic						
Input Capacitance	C_{iss}	-	2400	-	pF	V_{GS}=0V, V_{DS}=100V, f=1MHz
Output Capacitance	C_{oss}	-	144	-		
Reverse Transfer Capacitance	C_{rss}	-	2.5	-		
Gate Total Charge	Q_g	-	65	-	nC	V_{GS}=10V, V_{DS}=480V, I_D=23A
Gate-Source charge	Q_{gs}	-	22	-		
Gate-Drain charge	Q_{gd}	-	35	-		
Gate plateau voltage	$V_{plateau}$	-	8.1	-	V	
Turn-on delay time	$t_{d(on)}$	-	65	-	ns	V_{GS}=10V, I_D=23A, V_{DS}=400V, R_g=27Ω
Rise time	t_r	-	91	-		
Turn-off delay time	$t_{d(off)}$	-	150	-		
Fall time	t_f	-	40	-		
Gate resistance	$R_{g,int}$	-	1.2	-	Ω	f=1MHz

©China Resources Microelectronics (Chongqing) Limited

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	0.7	0.91	1.1	V	V_{GS}=0V,I_{SD}=23A
Body Diode Reverse Recovery Time	t_{rr}	-	125		ns	I_{SD}=23A di_F/dt=100A/μs V_{DS}=400V
Body Diode Reverse Recovery Charge	Q_{rr}	-	0.9		μC	

©China Resources Microelectronics (Chongqing) Limited

Typical Performance Characteristics

Fig 1. Output Characteristics (T_j=25℃)




Fig 2. Output Characteristics (T_j=150℃)




Fig 3: Transfer Characteristics




Fig 4: V_{TH} vs. T_j Temperature Characteristics




Fig 5: $R_{DS(on)}$ vs. I_{DS} Characteristics(T_j=25℃)





Fig 6: $R_{DS(on)}$ vs. Temperature



©China Resources Microelectronics (Chongqing) Limited

Fig 7: BV_{DSS} vs. Temperature




Fig 8: $R_{DS(on)}$ vs. Gate Voltage




Fig 9: Body-diode Forward Characteristics




Fig 10: Gate Charge Characteristics




Fig 11: Capacitance Characteristics






Fig 12: Safe Operating Area



©China Resources Microelectronics (Chongqing) Limited


Fig 13: Max. Transient Thermal Impedance




©China Resources Microelectronics (Chongqing) Limited

Test Circuit & Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms



©China Resources Microelectronics (Chongqing) Limited

Package Outline: TO-247-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	4.70	5.30	0.185	0.209
A1	2.20	2.60	0.087	0.102
A2	1.50	2.49	0.059	0.098
b	1.04	1.33	0.041	0.052
b2	1.90	2.41	0.075	0.095
b4	2.87	3.43	0.113	0.135
c	0.55	0.70	0.022	0.028
D	20.70	21.30	0.815	0.839
D1	16.25	17.65	0.640	0.695
D2	0.51	1.40	0.020	0.055
e	5.44 BSC.		0.214 BSC.	
E	15.50	16.30	0.610	0.642
E1	13.08	14.16	0.515	0.557
E2	3.80	5.49	0.150	0.216
E3	1.00	2.75	0.039	0.108
L	19.72	20.32	0.776	0.800
L1	3.85	4.50	0.152	0.177
Q	5.25	6.25	0.207	0.246
P	3.50	3.70	0.138	0.146
S	6.04	6.30	0.238	0.248

©China Resources Microelectronics (Chongqing) Limited

Marking



NOTE:
NXBBAAAA

N	—WB code (Usually omitted)
X	—Assembly location code
BB	—Fab code
AAAA	—Lot code

©China Resources Microelectronics (Chongqing) Limited

Revision History

Revison	Date	Major changes
2.0	2023/7/12	Update electrical characteristic

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qulified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semicondutor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.

©China Resources Microelectronics (Chongqing) Limited