华润微电子(重庆)有限公司

CRSZ019N10N4

SkyMOS4 N-MOSFET 100V, 1.75mΩ, 248A

Features

- Uses CRM(CQ) advanced SkyMOS4 technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent Q_gx$R_{DS(on)}$ product(FOM)
- Qualified according to JEDEC criteria

Product Summary

V_{DS}	100V
$R_{DS(on)}$	1.75mΩ
I_D	248A


Applications

- Motor control and drive
- Battery management
- UPS (Uninterrupible Power Supplies)


100% DVDS Tested

100% Avalanche Tested

RoHS HF



CRSZ019N10N4



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRSZ019N10N4	-	TOLL	Tape&Reel	N/A	N/A	-

Absolute Maximum Ratings

Parameter	**Symbol**	**Value**	**Unit**
Drain-source voltage	V_{DS}	100	V
Continuous drain current T_C = 25°C (Silicon limit) T_C = 25°C (Package limit) T_C = 100°C (Silicon limit)	I_D	 262 248 166	A
Pulsed drain current (T_C = 25°C, t_p limited by T_{jmax})	$I_{D\ pulse}$	992	A
Avalanche energy, single pulse (L=0.5mH, Rg=25Ω)[1]	E_{AS}	500	mJ
Gate-Source voltage	V_{GS}	±20	V
Power dissipation (T_C = 25°C)	P_{tot}	250	W
Operating junction and storage temperature	T_j , T_{stg}	-55...+150	°C

Notes:1.EAS was tested at Tj = 25℃, ID = 45A.

©China Resources Microelectronics (Chongqing) Limited

Thermal Resistance

Parameter	Symbol	Max	Unit
Thermal resistance, junction – case.	R_{thJC}	0.50	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	55	

Electrical Characteristic (at Tj = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV_{DSS}	100	-	-	V	V_{GS}=0V, I_D=250uA
Gate threshold voltage	$V_{GS(th)}$	2.2	3	3.8	V	V_{DS}=V_{GS},I_D=250uA
Zero gate voltage drain current	I_{DSS}	- -	0.05 -	1 100	μA	V_{DS}=100V,V_{GS}=0V T_j=25°C T_j=150°C
Gate-source leakage current	I_{GSS}	-	±10	±100	nA	V_{GS}=±20V,V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$	-	1.75	2.1	mΩ	V_{GS}=10V, I_D=100A
Transconductance	g_{fs}	-	275	-	S	V_{DS}=5V,I_D=100A
Dynamic Characteristic						
Input Capacitance	C_{iss}	7565	11347	17021	pF	V_{GS}=0V, V_{DS}=50V, f=1MHz
Output Capacitance	C_{oss}	1167	1751	4376		
Reverse Transfer Capacitance	C_{rss}	25	37	259		
Gate Total Charge	Q_G	100	157	200	nC	V_{GS}=10V, V_{DS}=50V, I_D=100A, f=1MHz
Gate-Source charge	Q_{gs}	30	66	100		
Gate-Drain charge	Q_{gd}	12	18	35		

©China Resources Microelectronics (Chongqing) Limited

Turn-on delay time	$t_{d(on)}$	19	29	43	ns	V_{GS}=10V, V_{DD}=50V, R_{G_ext}=3.0Ω
Rise time	t_r	76	114	170		
Turn-off delay time	$t_{d(off)}$	52	78	117		
Fall time	t_f	72	109	163		
Gate resistance	R_G	1	1.6	2.5	Ω	V_{GS}=0V, V_{DS}=0V, f=1MHz

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.9	1.4	V	V_{GS}=0V,I_{SD}=100A
Body Diode Continuous Forward Current	I_S	-	-	248	A	T_C = 25°C
Body Diode Pulsed Current	$I_{S\ pulse}$	-	-	992	A	T_C = 25°C
Body Diode Reverse Recovery Time	t_{rr}	49	99	197	ns	I_F=100A, dI/dt=100A/μs
Body Diode Reverse Recovery Charge	Q_{rr}	109	218	436	nC	

©China Resources Microelectronics (Chongqing) Limited

Typical Performance Characteristics

Fig 1: Output Characteristics





Fig 2: Transfer Characteristics



3: Rds(on) vs Drain Current and Gate Voltage




Fig 4: Rds(on) vs Gate Voltage




Fig 5: Rds(on) vs. Temperature





Fig 6: Vgs(th) vs. Temperature



©China Resources Microelectronics (Chongqing) Limited

Fig 7: BVds vs. Temperature




Fig 8: Capacitance Characteristics




Fig 9: Gate Charge Characteristics




Fig 10: Body-diode Forward Characteristics




Fig 11: Power Dissipation





Fig 12: Drain Current Derating



©China Resources Microelectronics (Chongqing) Limited

Fig 13: Safe Operating Area






Fig 13: Max. Transient Thermal Impedance




©China Resources Microelectronics (Chongqing) Limited


Test Circuit & Waveform


Gate Charge Test Circuit & Waveform







Resistive Switching Test Circuit & Waveforms







Unclamped Inductive Switching (UIS) Test Circuit & Waveforms






Diode Recovery Test Circuit & Waveforms






©China Resources Microelectronics (Chongqing) Limited

Package Outline: TOLL





SIDE VIEW

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.15	2.45	0.085	0.096
b	0.60	0.90	0.024	0.035
b1	9.65	9.95	0.380	0.392
c	0.35	0.65	0.014	0.026
D	10.18	10.70	0.401	0.421
D1	3.15	3.45	0.124	0.136
E	9.70	10.10	0.382	0.398
E1	7.35	8.45	0.289	0.333
e	1.10	1.30	0.043	0.051
H	11.45	11.95	0.451	0.470
H1	6.55	7.50	0.258	0.295
L	1.35	2.10	0.053	0.083
L1	0.50	0.90	0.020	0.035
L2	0.40	0.80	0.016	0.031
L3	0.95	1.35	0.037	0.053

©China Resources Microelectronics (Chongqing) Limited

Revision History

Revison	Date	Major changes
1.1	25/07/2022	update POD.

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qulified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semicondutor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.

©China Resources Microelectronics (Chongqing) Limited