CRSM062N10N

SkyMOS1 N-MOSFET 100V, 5.7mΩ, 79A

Features

- Uses CRM(CQ) advanced SkyMOS1 technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent Q_gx$R_{DS(on)}$ product(FOM)
- Qualified according to JEDEC criteria


Product Summary

V_{DS}	100V
$R_{DS(on)@10V\ typ}$	5.7mΩ
I_D	79A


Applications

- Synchronous Rectification for AC/DC Quick Charger
- Battery management
- UPS (Uninterrupible Power Supplies)

100% Avalanche Tested



CRSM062N10N



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRSM062N10N	-	DFN5X6	Tape&Reel	N/A	N/A	5000pcs

Absolute Maximum Ratings

Parameter	**Symbol**	**Value**	**Unit**
Drain-source voltage	V_{DS}	100	V
Continuous drain current T_C = 25°C (Silicon limit) T_C = 25°C (Package limit) T_C = 100°C (Silicon limit)	I_D	 79 80 50	A
Pulsed drain current (T_C = 25°C, t_p limited by T_{jmax})	$I_{D\ pulse}$	316	A
Avalanche energy, single pulse (L=0.3mH, Rg=25Ω)	E_{AS}	135	mJ
Gate-Source voltage	V_{GS}	±20	V
Power dissipation (T_C = 25°C)	P_{tot}	79	W
Operating junction and storage temperature	T_j , T_{stg}	-55...+150	°C

©China Resources Microelectronics (Chongqing) Limited

Thermal Resistance

Parameter	Symbol	Max	Unit
Thermal resistance, junction – case.	R_{thJC}	1.58	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	47.0	

Electrical Characteristic (at Tj = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV_{DSS}	100	-	-	V	V_{GS}=0V, I_D=250uA
Gate threshold voltage	$V_{GS(th)}$	2.2	3	3.8	V	V_{DS}=V_{GS},I_D=250uA
Zero gate voltage drain current	I_{DSS}	- -	- -	1 10	μA	V_{DS}=100V,V_{GS}=0V T_j=25°C T_j=125°C
Gate-source leakage current	I_{GSS}	-	-	±100	nA	V_{GS}=±20V,V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$		5.7	6.8	mΩ	VGS=10V,I_D=40A
Transconductance	g_{fs}	-	81	-	S	V_{DS}=5V,I_D=40A
Dynamic Characteristic						
Input Capacitance	C_{iss}	-	4135	-	pF	V_{GS}=0V, V_{DS}=50V, f=1MHz
Output Capacitance	C_{oss}	-	532	-		
Reverse Transfer Capacitance	C_{rss}	-	44	-		
Gate Total Charge	Q_G	-	65	-	nC	V_{GS}=10V, V_{DS}=50V, I_D=40A, f=1MHz
Gate-Source charge	Q_{gs}	-	24.8	-		
Gate-Drain charge	Q_{gd}	-	15.0	-		
Turn-on delay time	$t_{d(on)}$	-	20.4	-	ns	V_{GS}=10V, V_{DD}=50V, R_{G_ext}=3.0Ω
Rise time	t_r	-	85.3	-		
Turn-off delay time	$t_{d(off)}$	-	36.3	-		
Fall time	t_f	-	51	-		
Gate resistance	R_G	-	1.4	-	Ω	V_{GS}=0V, V_{DS}=0V, f=1MHz

©China Resources Microelectronics (Chongqing) Limited

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	0.88	1.4	V	V_{GS}=0V,I_{SD}=40A
Body Diode Reverse Recovery Time	t_{rr}	-	61.9	-	ns	I_F=40A, dI/dt=300A/μs
Body Diode Reverse Recovery Charge	Q_{rr}	-	318	-	nC	

©China Resources Microelectronics (Chongqing) Limited

Typical Performance Characteristics

Fig 1: Output Characteristics





Fig 2: Transfer Characteristics



3: Rds(on) vs Drain Current and Gate Voltage




Fig 4: Rds(on) vs Gate Voltage




Fig 5: Rds(on) vs. Temperature




Fig 6: Capacitance Characteristics




Fig 7: Gate Charge Characteristics




Fig 8: Body-diode Forward Characteristics




Fig 9: Power Dissipation




Fig 10: Drain Current Derating




Fig 11: Safe Operating Area







Fig 12: Max. Transient Thermal Impedance




Test Circuit & Waveform


Gate Charge Test Circuit & Waveform







Resistive Switching Test Circuit & Waveforms







Unclamped Inductive Switching (UIS) Test Circuit & Waveforms






Diode Recovery Test Circuit & Waveforms





Package Outline: DFN5X6



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.80	1.20	0.031	0.047
A1	0.00	0.05	0.000	0.002
b	0.30	0.51	0.012	0.020
c	0.15	0.35	0.006	0.014
D	4.80	5.40	0.189	0.213
e	1.27 BSC		0.050 BSC	
E	5.66	6.06	0.223	0.239
G	0.30	0.71	0.012	0.028
H	5.90	6.35	0.232	0.250
J	3.32	3.92	0.131	0.154
K	3.61	4.25	0.142	0.167
L1	0.05	0.25	0.002	0.010
L2	0.00	0.15	0.000	0.006
R	0.25 REF		0.010 REF	
θ	0°	12°	0°	12°

©China Resources Microelectronics (Chongqing) Limited

Revision History

Revison	Date	Major changes
1.0	2018-10-22	Release of formal version.
2.0	2019-6-25	Supplement package outline info.

Disclaimer

Unless otherwise specified in the datasheet, the product is designed and qulified as a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability, such as automotive, aviation/aerospace and life-support devices or systems.

Any and all semicondutor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

CRM(CQ) reserves the right to improve product design, function and reliability without notice.