Features

- Uses CRM(CQ) advanced Trench technology
- Extremely low on-resistance $R_{DS(on)}$
- Excellent Q_gx$R_{DS(on)}$ product(FOM)
- AEC-Q101 Qualified
- MSL1 up to 260°C peak reflow

Product Summary


V_{DS}	-100V
$R_{DS(on)@10V\ typ}$	72mΩ
I_D	-18A

Applications


- Motor control and drive
- Battery management
- UPS (Uninterrupible Power Supplies)

100% DVDS Tested

100% Avalanche Tested



CRTD680P10LQ



Package Marking and Ordering Information

Part #	Marking	Package	Packing	Reel Size	Tape Width	Qty
CRTD680P10LQ	680P10LQ	TO-252	Tape&reel	N/A	N/A	2500pcs

Absolute Maximum Ratings

Parameter	**Symbol**	**Value**	**Unit**
Drain-source voltage	V_{DS}	-100	V
Continuous drain current T_C = 25°C (Silicon limit) T_C = 25°C (Package limit) T_C = 100°C (Silicon limit)	I_D	 -18 -80 -11	A
Pulsed drain current (T_C = 25°C, t_p limited by T_{jmax})	$I_{D\ pulse}$	-73	A
Avalanche energy, single pulse (ID=-17A, Rg=25Ω)[1]	E_{AS}	72	mJ
Gate-Source voltage	V_{GS}	±20	V
Power dissipation (T_C = 25°C)	P_{tot}	60	W
Operating junction and storage temperature	T_j , T_{stg}	-55...+150	°C
Soldering temperature, wave soldering only allowed at leads (1.6mm from case for 10s)	Tsold	260	°C

Notes:1.EAS was tested at Tj = 25℃, L = 0.5mH, IAS = -17A, Vgs=-10V.

Thermal Resistance

Parameter	**Symbol**	**Max**	**Unit**
Thermal resistance, junction – case (junction-heat-spreader)	R_{thJC}	2.1	°C/W
Thermal resistance, junction – ambient(min. footprint)	R_{thJA}	62	
Thermal resistance, junction – plastic case	$R_{thJ\text{-}pc}$	36	

©China Resources Microelectronics (Chongqing) Limited

Electrical Characteristic (at Tj = 25 °C, unless otherwise specified)

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Static Characteristic						
Drain-source breakdown voltage	BV_{DSS}	-100	-	-	V	V_{GS}=0V, I_D=-250uA
		-100	-	-	V	V_{GS}=0V, I_D=-1mA
Gate threshold voltage	$V_{GS(th)}$	-1	-2	-3	V	V_{DS}=V_{GS},I_D=-250uA
Zero gate voltage drain current	I_{DSS}	-	-	-1	μA	V_{DS}=-100V,V_{GS}=0V T_j=25°C
		-	-	-100		T_j=125°C
Gate-source leakage current	I_{GSS}	-	-	±100	nA	V_{GS}=±20V,V_{DS}=0V
Drain-source on-state resistance	$R_{DS(on)}$	-	72	90	mΩ	V_{GS}=-10V, I_D=-10A
			80	120		VGS=-4.5V, ID=-5A
Transconductance	g_{fs}	11	22	44	S	V_{DS}=-5V,I_D=-10A
Dynamic Characteristic						
Input Capacitance	C_{iss}	1246	2491	4982	pF	V_{GS}=0V, V_{DS}=-50V, f=1MHz
Output Capacitance	C_{oss}	17	86	431		
Reverse Transfer Capacitance	C_{rss}	13	63	315		
Gate Total Charge	Q_G	27	40	61	nC	V_{GS}=-10V, V_{DS}=-50V, I_D=-10A, f=1MHz
Gate-Source charge	Q_{gs}	2	7	21		
Gate-Drain charge	Q_{gd}	3	9	18		
Turn-on delay time	$t_{d(on)}$	4	8	16	ns	V_{GS}=-10V, V_{DD}=-50V, R_{G_ext}=2.7Ω, Id=-10A
Rise time	t_r	10	20	40		
Turn-off delay time	$t_{d(off)}$	65	97	145		
Fall time	t_f	28	43	64		
Gate resistance	R_G	-	11	25	Ω	V_{GS}=0V, V_{DS}=0V, f=1MHz

Body Diode Characteristic

Parameter	Symbol	Value			Unit	Test Condition
		min.	typ.	max.		
Body Diode Forward Voltage	V_{SD}	-	-0.9	-1.3	V	V_{GS}=0V,I_{SD}=-10A
Body Diode Reverse Recovery Time	t_{rr}	18	35	70	ns	I_F=-10A, dI/dt=100A/μs
Body Diode Reverse Recovery Charge	Q_{rr}	31	61	123	nC	

©China Resources Microelectronics (Chongqing) Limited

Typical Performance Characteristics

Fig 1: Output Characteristics




Fig 2: Transfer Characteristics




Fig 3: Rds(on) vs Drain Current and Gate Voltage




Fig 4: Rds(on) vs Gate Voltage




Fig 5: Rds(on) vs. Temperature





Fig 6: Vgs(th) vs. Temperature



©China Resources Microelectronics (Chongqing) Limited

Fig 7: BVds vs. Temperature




Fig 8: Capacitance Characteristics




Fig 9: Gate Charge Characteristics




Fig 10: Body-diode Forward Characteristics




Fig 11: Power Dissipation





Fig 12: Drain Current Derating



©China Resources Microelectronics (Chongqing) Limited

Fig 13: Safe Operating Area






Fig 14: Max. Transient Thermal Impedance




©China Resources Microelectronics (Chongqing) Limited

Test Circuit & Waveform


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms




Diode Recovery Test Circuit & Waveforms



©China Resources Microelectronics (Chongqing) Limited

Package Outline: TO-252



Symbol	Dimensions In Millimeters		
	Min.	Nom.	Max.
A	2.15	2.30	2.45
A1	0.00	0.07	0.15
b	0.60	0.76	0.91
b1	0.65	--	1.15
b2	5.00	5.33	5.50
c	0.45	0.50	0.61
c1	0.36	0.50	0.66
D	5.80	6.10	6.22
D1	5.222	5.572	5.922
e		2.29 BSC.	
E	6.30	6.50	6.73
E1	4.75	5.10	5.45
H	9.40	9.90	10.48
L	1.38	1.52	1.78
L1		2.92 REF	
L2		0.508 BSC.	
L3	0.72	1.01	1.35
L4	0.60	0.75	1.20
θ	0°	--	8°

©China Resources Microelectronics (Chongqing) Limited

Marking



NOTE:
XAAAAAAA
X —Assembly location code
AAAAAAA —Assembly lot NO. last 7digits

Revision History

Revision	Date	Major changes
1.0	2023/5/22	Release of preliminary 1.0 version.
1.1	2023/6/25	Update Ciss/Coss/Crss spec.
2.0	2023/8/25	Update Marking

Disclaimer

CRM reserves the right to change any product or information in this Specification at any time without prior notice.

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics .The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

The product is not intended for use in applications that require extraordinary levels of quality and reliability, such as aviation/aerospace and life-support devices or systems.

Any and all semicondutor products have certain probability to fail or malfunction, which may result in personal injury, death or property damage. Customer are solely responsible for providing adequate safe measures when design their systems.

©China Resources Microelectronics (Chongqing) Limited